



SERVO[®] PRODUCT DATA SHEET

SERVO GREASE MP



IndianOil

GRADES AVAILABLE – SERVOGREASE MP, MP 3

DESCRIPTION

Servo Grease MP is a premium quality lithium soap, multi-purpose automotive grease, with high drop point, good thermal and structural stability and also having resistance against water wash out. With its smooth structure and high degree of resistance against oxidation and rusting/corrosion it is an ideal product for all grease lubricated parts of automotive equipment.

APPLICATION

Servo Grease MP is recommended for water pump, wheel bearings, chassis fittings and universal joints, including those of constant velocity type, for mobile equipment e.g., automotive, off- highway equipment such as tractors, construction equipment etc.

PERFORMANCE BENEFITS

- Provides excellent resistance to structural and consistency changes, over wide range of temperatures but remains in place despite severe working or sustained shock impact
- Has excellent low and high temperature properties. It can be dispensed at low temperatures and will maintain adequate stay-put property at the higher temperatures encountered in service
- Resists effectively, water wash out in use, assuring adequate lubrication over extended service periods
- Provides resistance to oxidation, rust and corrosion

PERFORMANCE STANDARDS

Servo Grease MP meets IS:12203:1987 (Reaffirmed 1993)

MANUFACTURER'S APPROVAL

Servo Grease MP is approved by the leading manufacturers, such as :

- Ashok Leyland Ltd., Madras
- Bharat Earth Movers Ltd., Bangalore
- Escorts Ltd. (Tractor Division), Faridabad
- Hindustan Machine Tools, (Tractor Division), Pinjore
- Premier Automobiles Ltd., Mumbai

CHARACTERISTICS

GRADE	Grease MP	Grease MP 3
Colour	Brown	Brown
Structure	Smooth	Smooth
Soap Type	Lithium	Lithium
Worked Penetration, @25°C, (60 Strokes)	270-310	220-250
Drop Point, °C Min.	180	180

HEALTH & SAFETY

These oils are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of industrial and personal hygiene are maintained.

For further information please contact our nearest office OR:

Technical Services Dept., Indian Oil Corporation Ltd., G-9, Ali Yavar Jung Marg, Bandra (East), Mumbai – 400 051

E-Mail: tservices@indianoil.co.in OR tech_services@indianoil.co.in