

SERVO SUPER DS

GRADES AVAILABLE – SERVO SUPER DS 30, 40, 50

<p>DESCRIPTION</p> <p>Servo Super DS oils are heavy duty engine oils for diesel service. These oils are blended from selected highly refined, high viscosity index base stocks and contain well balanced group of additives, to provide high detergency, dispersancy and anti oxidation characteristics to meet the stated performance standards.</p>	<p>APPLICATION</p> <p>Servo Super DS oils are recommended for:</p> <ul style="list-style-type: none"> Naturally aspirated, supercharged and turbocharged diesel engines. Mixed fleet operation
<p>PERFORMANCE BENEFITS</p> <p>Servo Super DS Oils</p> <ul style="list-style-type: none"> Provide excellent resistance against wear and deposits in automotive supercharged diesel engines Have exceptional thermal and oxidation stability to resist decomposition in supercharged engines operating with high ring zone temperature. Provide absolute control of corrosive wear that may result from use of high sulphur fuels because of good built-in alkaline reserves. Maintain a high order of engine cleanliness 	<p>PERFORMANCE STANDARDS</p> <p>Servo Super DS oils meet the following specifications:</p> <ul style="list-style-type: none"> US MIL-L 2104C API CF E-DL 3 of IS:13656-2002 Caterpillar Series 3 MACK T-7 test for oil thickening tendency. Sequence III F

CHARACTERISTICS

SAE GRADE	30	40	50
Kin. Vis. cSt @ 100°C	10 – 12	13 – 15	18 – 20
Viscosity Index, Min.	95	90	90
Flash point (COC), °C Min.	220	220	230
Pour Point, °C Max.	(-) 6	(-) 6	(-) 6
TBN mg KOH/gm	9.5–12.5	9.5–12.5	9.5–12.5

HEALTH & SAFETY

These oils are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of industrial and personal hygiene are maintained.