

SERVO XEE SJ

GRADES AVAILABLE - -SERVO XEE SJ 10W-30, 10W-40, 15W-40, 20W-50

DESCRIPTION

Servo XEE SJ oils are long life, high performance fuel economy engine oil for new generation petrol and diesel vehicles. These oils are blended from high viscosity index base stocks and contain additives to meet the highest quality performance standard

APPLICATION

Servo XEE SJ oils are recommended for new generation imported and Indian passenger cars using petrol.

PERFORMANCE BENEFITS

- ☞ Superior performance in terms of improved oil and engine life.
- ☞ Less oil thickening, better deposit control.
- ☞ Excellent Engine Cleanliness.
- ☞ Catalytic Convertor Compatible.

PERFORMANCE STANDARDS

- ☞ API SJ in gasoline and API CF in diesel service.
- ☞ ACEA A3/B3 – 96, VW 500.00/505.00, MB 229.1
- ☞ Fuel economy standards API EC II & EC I for 10W-30 and 10W-40 grade respectively.

CHARACTERISTICS

SAE GRADE	10W-30	10W-40	15W-40	20W-50
Kin.Viscosity @ 100°C, cSt	9.5 – 11.0	13.5 – 14.5	13.5 - 14.5	17.5 – 19.5
Viscosity Index, Min	130	140	130	130
Flash Point, COC, °C, Min	200	206	206	206
Pour Point, °C, Min.	(-) 30	(-) 27	(-) 24	(-) 21
TBN, mg KOH/gm	9 – 11	9 – 11	9 – 11	9 - 11

HEALTH & SAFETY

These oils are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of industrial and personal hygiene are maintained.

For further information please contact our nearest office OR:

Commercial & Lube Dept., Lanka IOC PLC, Level 20, West Tower, World Trade Center, Echelon Square, Colombo 01.

E-Mail: vsakthivel@lankaio.com OR lankaio.com