



SERVOGEM HTXX

GRADES AVAILABLE – SERVOGEM HTXX

DESCRIPTION

Servogem HTXX is a clay based grease. Servogem HTXX is greyish black, due to the addition of chemically stable Molybdenum disulphide. The presence of MoS₂, in Servogem HTXX makes it particularly suitable for lubrication of machine elements operating under high temperature conditions. High load bearing properties imparted by MoS₂ and special anti-wear, antioxidant additives, ensure full protection to lubricated parts.

PERFORMANCE BENEFITS

Servogem HTXX greases

- have excellent resistance to oxidation thereby enabling it to withstand sustained exposure to high temperatures
- Ensure minimum softening and loss of structure at high temperatures, even when subjected to substantial shear
- Have excellent resistance to water wash out
- Resist effect of mild acids and alkalies

APPLICATION

Servogem HTXX grease has been developed for the lubrication of machine elements, plain bearings and anti-friction bearings operating under high temperature conditions (between 120°C to 250°C). Servogem HTXX is recommended for calendar roll bearings of textile mills, paper mills and PVC filling machines, hot air exhausters/blowers, high temperature stuffing boxes etc.

Servogem HTXX is also recommended for soot blowers of power plants, slides and other moving parts of overhead cranes for soaking pits in steel mill, track rollers of earth moving equipment, billet feeder bearings in rolling mills and bogie cars in sintering plants, etc.

PERFORMANCE STANDARDS

Servogem HTXX grease meet US Steel requirement No. 372, IPSS 1-09-008 and IS:12790-1989

CHARACTERISTICS

GRADE	HTXX
Colour	Greyish Black
Structure	Smooth
Soap Type	Non-soap
Worked penetration, @ 25°C, (60 Strokes)	265-295
Drop Point, °C Min.	280
Weld Load in Kg, Min	225

HEALTH & SAFETY

These oils are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of industrial and personal hygiene are maintained.

For further information please contact our nearest office OR:

Commercial & Lube Dept., Lanka IOC PLC, Level 20, West Tower, World Trade Center, Echelon Square, Colombo 01.

E-Mail: vsakthivel@lankaio.com OR lankaio.com